
## DATA SHEET PM-1216/1217/1218A-9





		Specifications		
Direction indicato	r	Functi	ons:	LED direction i
		L	EDs:	9 x LEDs
[O] Images		Lens t	ype:	LumenX®
LumenX		Lens co	lour:	Amber
		Certificati	ons:	ECE Reg 6: E13 For front and r
		Volt	age:	Dual voltage 1
		IP ra	ting:	IP67
		Opera tempera		-30°C to +50°0
	Rear of light showing built-in AMP compatible receptacle & plug	Moun	ting:	PM-1216A & 1 PM-1217A-9 s series bracket o grommet PM-1218A-9 f
		Wi	ring:	Built-in AMP-c attachment to PM-417-48 or AMP Terminals
	PM-B426-18 grommet	Power ra	ting:	6.0W @ 12V /
Dimensions		Average cur d	rent raw:	0.50A @ 12V ,
		Reverse pol		Yes
0.82"	1.35"	Warra		3 years
0.82" 21 mm 5.57" 142 mm Bolt Hole Radius	1.35° 35mm	Ma	terials	5
2.56" 65 mm	4.25" 108 mm		Lens:	PMMA-HI
			Base:	ABS
Surface mount with	PM-1217A-9 light	Part numbe	ers	
bracket	module	PM-1216A-9	l l	rection indicator
1 35"		PM-1216AC-9	LED dir bracket	rection indicator t
1.35° 35mm		PM-1217A-9		rection indicator ories below)
( 4.25" 108 mm 5.50" 140 mm 15.50"	5.25" 133 mm	PM-1218A-9	LED dir	rection indicator
108 mm 140 mm 115 mm		PM-B817-09	Black bracket for PM-	
		PM-B817-10	Chrome	e bracket for PN
Flange mount	25 mm PM-B426-18	PM-B426-18	Gromm	net for PM-1217
	grommet	PM-B417-48	2 wire p	olug
		DIA DOAT AC	10 .	1 / 11 15

## Specifications

Functions:	LED direction indicator light	
LEDs:	9 x LEDs	
Lens type:	LumenX®	
Lens colour:	Amber	
Certifications:	ECE Reg 6: E13 06R00 06R01 14137 00 For front and rear use	
Voltage:	Dual voltage 12/24Vdc	
IP rating:	IP67	
Operating temperature:	-30°C to +50°C	
Mounting:	PM-1216A & 1216AC surface mount with bracket PM-1217A-9 surface mounts using a PM-817 series bracket or flush mounts using PM-B426-18 grommet PM-1218A-9 flange mounts	
Wiring:	Built-in AMP-compatible receptacle for direct attachment to body harness, or requires PM-417-48 or PM-817-48 plug AMP Terminals: T1 = ground T2 = not used T3 = indicator	
Power rating:	6.0W @ 12V / 6.0W @ 24V	
Average current draw:	0.50A @ 12V / 0.25A @ 24V	
Reverse polarity protection:	Yes	
Warranty:	3 years	

Part numbers		
PM-1216A-9	LED direction indicator light- surface mount, black bracket	
PM-1216AC-9	LED direction indicator light- surface mount, chrome bracket	
PM-1217A-9	LED direction indicator light module - (see mounting accessories below)	
PM-1218A-9	LED direction indicator light - flange mount	
PM-B817-09	Black bracket for PM-1217A-9 (surface mounting)	
PM-B817-10	Chrome bracket for PM-1217A-9 (surface mounting)	
PM-B426-18	Grommet for PM-1217A-9 (flush mounting)	
PM-B417-48	2 wire plug	
PM-B817-48	2 wire plug (moulded)	

