DATA SHEET



PM-M1202 series LED outline & side markers

Specifications - PM-M1202A Side marker light


Functions:	Side marker light with integral reflex reflector
LEDs:	4 diodes
Certifications:	ECE Reg 91: SM1-E9-00.1221 ECE Reg: 3: IA-E9-02.1221
Dimensions:	70mm L x 19mm W x 16mm H
Voltage:	12V and 24V versions
IP rating:	IP67
Operating temperature:	-30°C to + 50°C
Mounting:	Surface mounted May be mounted horizontally or vertically Optional mounting accessories available
Cables:	225mm long flying leads
Power rating:	0.5W @ 12V / 1.0W @ 24V
Current draw:	0.045A @ 14V / 0.05A @ 28V
Reverse polarity protection:	Yes
Warranty:	3 years



or	is -	PM-M120 Outline m			20	2R	
				• • •			l

	Functions:	Front & rear outline marker lights with integral reflex reflector
	LEDs:	4 diodes
	Certifications:	PM-M1202C ECE Reg 7: A-E9-02.1243 Reg 3. IA-E9-02.1243
79"		PM-M1202R ECE Reg 7: R-E9-02.1242 Reg 3. IA-E9-02.1242
mm	Dimensions:	70mm L x 19mm W x 16mm H
'n	Voltage:	PM-M1202C: 24V PM-M1202R: 12V & 24V versions available
	IP rating:	IP67
	Operating temperature:	-30°C to + 50°C
	Mounting:	Surface mounted May be mounted horizontally or vertically
	Cables:	225mm long flying leads
	Power rating:	2.0W @ 12V / 2.0W @ 24V
	Current draw:	PM-M1202C-MV: / 0.04A @ 28V PM-M1202R-MV: 0.16A @ 14V / 0.028A @ 28V
	Reverse polarity protection:	Yes
	Warranty:	3 years
Ć	Materials	
	Lens:	РММА-НІ

PM-B1202-09V Dimensions



1202A



Part numbers

PM-M1202A-12V	Side marker, amber, 12V
PM-M1202A-24V	Side marker, amber, 24V
PM-M1202C-24V	Front outline marker, white, 24V
PM-M1202R-12V	Rear outline marker, red, 12V
PM-M1202R-24V	Rear outline marker, red, 24V
PM-B1202-09V	Vertical bracket
PM-B1202-09H	Horizontal bracket

sales@petersoneurope.co.uk sales@petersoneurope.eu petersoneurope.com petersoneurope.eu

